

FS-2000D

A4 MONOCHROME PRINTER

► print ► copy ► scan ► fax

MORE SPACE TO THINK ABOUT ESSENTIALS.

This new generation team printer offers standard double-sided printing. When configured with the optional network interface it can handle a small workgroup and supports a wide range of paper types and formats. Low noise, compact design and cost-effective ECOSYS technology give you space to think about the bigger picture.

- 30 pages per minute with true 1,200 dpi
- 64 MB memory standard, upgradeable to 576 MB
- PDF direct printing from USB Flash Memory devices
- Eco-friendly, ozone-free technology
- Long-life components and easy maintenance

Offers the possibility to upgrade paper capacity to 1,100 sheets and handles a variety of paper sizes and weights for demanding workgroups.



A user-friendly backlit LCD display is positioned to the right of the paper output for easier access to your work.



ECOSYS[®]

 **KYOCERA**

FS-2000D

A4 MONOCHROME PRINTER



ECOSYS devices are designed to minimise both direct costs and indirect costs, such as maintenance, administration and consumables. The cartridge-free system requires only the toner to be replaced. The modular design concept allows you to add workflow-enhancing functions and a wide variety of paper handling capabilities as required. Integrated system software provides long-term cross-network compatibility. Kyocera's long-life components cost you and the environment less.

GENERAL

Technology: Kyocera ECOSYS, Laser
Engine speed: Up to 30 pages per minute A4 simplex
Up to 15.5 pages per minute A4 duplex
Resolution: True 1,2000 dpi
Time to first page: 9 seconds or less
Warm-up time: 13 seconds or less from power on
Duty cycle: Max. 150,000 pages per month,
max. average 20,000 pages per month
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption: Printing: 400 W, Stand-by: 9 W,
Power-Saving (ECOpower): 4.4 W
Noise (ISO 7779): Printing: 50 dB(A), Stand-by: 29 dB(A),
Power-Saving (ECOpower): Immeasurably low
Dimensions (W x D x H): Main unit: 382 x 394 x 285 mm
Weight: Main unit: Approx. 15.8 kg
Certifications: TÜV/GS, CE, PTS
This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 500-sheet universal paper cassette, 60-120 g/m², A4, A5, B5, Letter, Legal, Custom (148 x 210 mm to 216 x 356 mm)
100-sheet multi-purpose tray, 60-220 g/m², A4, A5, A6, B5, Letter, Legal, Custom (70 x 148 mm to 216 x 356 mm)
Max. input capacity with optional paper feeder PF-310: 1,100 sheets
Duplex as standard supports A4, A5, B5, Letter, Legal, 60-120 g/m²
Output capacity: 250 sheets face-down with paper full sensor

CONTROLLER

Processor: PowerPC 440 / 400 MHz
Memory: Standard 64 MB + ECOMemory, max. 576 MB
Emulations: PCL6/PCL5e incl. PJI, KPDL 3 (PostScript 3 compatible), PDF direct print, Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630
Controller language: PRESCRIBE IIe
Fonts: 80 outline fonts accessible in all emulations, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode PDF-417, Downloadable fonts: Kyocera, PCL + TrueType format, Type 1 + 3 format
Print features: Duplex, Accounting, PDF direct printing, eMPS, low noise, no Ozone, USB-Host

System platform:

The FS-2000D offers USB and parallel connectivity as standard as well as optional network connectivity and delivers problem-free system administration. Kyocera's single platform technology means that the same driver can be used for every Kyocera PCL/PostScript print device on the network; from single-user desktop printers to high-end multifunctional systems. Only Kyocera offers this effortless combination of IT sophistication and high-performance paper handling expertise.

PRESCRIBE IIe:

With the Kyocera page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (even multipart forms) can be created independently of the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

KM-NET for Client/KM-NET Viewer:

The settings of all printers on the network can be checked visually and amended from any Windows® PC. KM-NET for Client enables easy setup and monitoring of the printer status via parallel, USB or optional network connection. KM-NET Viewer is an advanced printer management software tool using the standardized protocol SNMP.

INTERFACES

Standard interface: High speed bi-directional parallel (IEEE 1284), USB 2.0 (Hi-Speed), USB Host Interface dedicated for USB Flash Memory device, KUIO-LV option interface slot
Multiple interface connection (MIC): Allows simultaneous data transfer via up to three interfaces, with each interface having its own virtual printer.

OPTIONS

Paper handling

PF-310 Paper feeder (max. 1 unit): 500 sheets, 60-120 g/m², A4, A5, B5, Letter, Legal, Custom (148 x 210 mm to 216 x 356 mm)

CB-310 Printer cabinet: Desk with storage capacity

Memory

Printer memory: 1 DDR SDRAM DIMM slot (64, 128, 256 or 512 MB)

Storage memory: 1 slot for either CompactFlash® memory card type 1 (up to 2 GB) for forms, fonts, logos, macro storage or Microdrive™ (up to 4 GB) for forms, fonts, logos, macro storage as well as document management with eMPS functions such as quick copy, proof and hold, private print and job storage.

1 USB Host Interface (USB 1.1) for USB Flash Memory device supports PDF direct printing

Optional interface

IB-30/IB-21E Network card: 10Base-T/100Base-TX

SB-50 Network card: 10Base-FL, FibreLink

SB-60 Network card: TokenRing STP/UTP

SB-70 Network card: Wireless LAN – IEEE 802.11b

SB-110FX Network card: 10Base-T/100Base-TX/100Base-FX, FibreOptic

SB-140 Network card: 10Base-2/10Base-T/100Base-TX

SB-80 Parallel interface: 2nd parallel interface – IEEE 1284

IB-11 Serial interface: RS-232C serial interface

(max. 115.2 kbps)

CONSUMABLES

TK-310 Toner kit: Microfine toner for 12,000 pages with 5% coverage (ISO/IEC 19752)

Capacity of starter toner is 6,000 pages with 5% coverage (ISO/IEC 19752)

WARRANTY

2-year warranty as standard. Kyocera guarantees the drum and developer for 3 years or 300,000 pages (whichever occurs sooner), provided each printer is used and cleaned in accordance with the service instructions.



Up to 5-year on-site warranty extensions available for printer and options.

MODEL CONFIGURATIONS

FS-2000DN (FS-2000D + Network card: 10Base-T/100Base-TX)



Select your options to suit your needs:

Paper feeder (PF-310)



Product depicted includes optional extras

Your Kyocera Business Partner:

Kyocera Mita Europe B.V., Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands, Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256, www.kyoceramita-europe.com, info@kyoceramita-europe.com
Kyocera Mita Corporation, 2-28, 1-Chome, Tamatsukuri, Chuo-Ku, Osaka 540-8585, Japan, www.kyoceramita.com

FS-2000D-English-8DSE2000. Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

